

25 kV Class Elbow Arrester (8.4 kV MCOV)

By Hubbell Power Systems
Catalog # [225ELA10](#)

Deadfront Elbow Arrester.

Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator No

Current

Duty Cycle	10 kV
Maximum Switching Surge	24.0 kV
Protective Level @ 500A	
Maximum Discharge Voltage	• 27 kV @ 1.5 kA • 29.5 kV @ 3 kA • 31.5 kV @ 5 kA • 36 kV @ 10 kA • 41.5 kV @ 20 kA • 53 kV @ 40 kA
kV Class	25 kV
MCOV	8.4 kV

Dimensions



Width	3.0625 in
Weight	3.700 lb.
Height	10.875 in
Length	7.75 in
Dimensions	7.75 in x 3.0625 in x 10.875 in

General

Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
Material type	Standard
UPC	096359360575

Logistics

Standard Package	1
------------------	---

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)