

15 kV Class Elbow Arrester (7.65 kV MCOV)

By Hubbell Power Systems
Catalog # 215ELA09

Deadfront Elbow Arrester.

Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator	No
Current	
Maximum Switching Surge	23.0 kV
Protective Level @ 500A	
MCOV	7.65 kV
Duty Cycle	9 kV
Maximum Discharge Voltage	• 26.8 kV @ 1.5 kA • 28 kV @ 3 kA • 30 kV @ 5 kA • 33 kV @ 10 kA • 39 kV @ 20 kA • 50.5 kV @ 40 kA
kV Class	15 kV

Dimensions



Length	8.438 in
Width	2.85 in
Weight	3.700 lb.
Height	9.438 in
Dimensions	8.438 in x 2.85 in x 9.438 in

General

Material type	Standard
Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
UPC	096359266624

Logistics

Standard Package	1
Pallet Quantity	160

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)