

35 kV Class Small Interface Elbow Arrester
(19.5 kV MCOV)

By Hubbell Power Systems
Catalog # [235ELA24](#)

Small Interface Elbow Arrester, 35kV 19.5 MCOV



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator	No
Buy America(n) Qualified	Contact Manufacturer

Current

Maximum Switching Surge	63.0 kV
Protective Level @ 500A	
MCOV	19.5 kV
Duty Cycle	24 kV
Maximum Discharge Voltage	• 71.5 kV @ 1.5 kA • 76.5 kV @ 3 kA • 82 kV @ 5 kA • 90.5 kV @ 10 kA • 106.5 kV @ 20 kA • 138 kV @ 40 kA
kV Class	35 kV

Dimensions

Length	10.375 in
Width	3.625 in
Weight	5.200 lb.
Height	12.875 in
Dimensions	10.375 in x 3.625 in x 12.875 in

General

Material type	Standard
Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
UPC	096359433415

Logistics

Standard Package	1
Pallet Quantity	64

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)