BURNDY

# YDS36R, 2-piece, ACSR Splice, includes inner and outer sleeves



By Burndy
Catalog # YDS36R

2-piece, full tension ACSR splice consists of steel inner sleeve and AL outer sleeve, Inner Sleeve: 7.88 IN L, Outer Sleeve: 26.38 IN L

## Features

- 2-Piece, Full Tension HYSPLICE consists of aluminum outer sleeve and steel inner sleeve
- Tapered out sleeve provides gradual transition of stress
- Filler hole provided for PENETROX Joint Compound
- Sizes 1/0 and larger come supplied with plugs for filler hole

## Application

For ACSR, Compressed And Compact Conductors

## Specifications

| | |
|---|---|
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | No |
| UL Listed | No |

## Conductor

| | |
|---|---|
| Conductor - ACSR Str Size | 477.0 (26/7) Hawk kcmil |
| Conductor - ACSR Str Size Range | 477.0 (26/7) Hawk kcmil |
| Conductor Type | • ACSR C Str-Size<br>• AL C Str-Size |

## Configuration

| | |
|---|---|
| Connector Type | Splice |

## Dimensions

| | |
|---|---|
| Dimension - L Length Overall mm | 200 mm |
| Dimension - Steel Sleeve Length inch | 7.875 in |
| Dimension - Aluminum Sleeve Length inch | 26.375 in |
| Dimension - Length Overall inch | 7.89 in |

## General

| | |
|---|---|
| Die Index | • 350<br>• 261 |
| Trade Name | HYSPLICE™ |
| Prefilled Oxide Inhibitor | Y |
| Die Index - Element A | 350 |
| Die Index - Element B | 261 |
| Sub Brand | HYSPLICE |
| Plated | N |
| Type | YDS-R Set |
| UPC 12 Digit | 781810015759 |
| UPC 14 Digit GTIN | 00781810015759 |
| Material | Aluminum |
| Plating Type | Unplated |
| UPC | 781810015759 |

## Logistics

| | |
|---|---|
| Carton Quantity | 10 |
| Pallet Quantity | 350 |

## Product Assets

Catalog [English]



© 2026 Hubbell Incorporated. All rights reserved