



Wiremold
BLANKING PLATE 1.25IN IPS BRASS
Part No. 1046B

Walkerduct® Underfloor Duct System includes two sizes of underfloor ducts - No.2 and No. 4 - for maximum flexibility. This allows you to match cable capacity to project demands by combining several ducts of different sizes in the same system. It's an ideal configuration for casinos, commercial offices, education, government, museums, and retail applications. Walkerduct features superior product construction, manufactured of 16-gauge galvanized steel with continuous seam welds. It accepts a wide variety of service fittings, including flush and pedestal styles. Ducts are available with or without presets. Pro Series presets are rectangular and accommodate flush and pedestal service fittings while providing ample bend radius to ensure the integrity of fiber optic cable connections. IPS presets are round and offer smaller egress areas. These work with pedestal style activations and are ideal for furniture feed applications. See page 17 for more information on compatible service fittings. Walkerduct can be fed by junction boxes or by Trenchduct for larger cable capacity installations.

Features & Benefits

Blanking plate. 3 1/2" [89mm] diameter top plate for 1-1/4" IPS. Brass

Specifications

General Info

Product Line	Wiremold	UPC Number	786564222002
Country Of Origin	United States	Construction	Not Assembled
Application Sector	Commercial	Standard	cULus Listed Underfloor Raceway Fittings: File E11912 Guide RQKX Meets Articles 390 of NEC
Warranty Type	1-Year from Installation or 2-Years from Day of Sale		

Dimensions

Product Width US	3.625 in	Product Weight US	0.266 lb
Product Length US	3.625 in		

Additional Information

RoHS Compliant Yes
