



PANDUIT PART NO.	BUNDLE DIA.		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	MIN. LOOP TENSILE lbs. (N)	CROSS SECTION	TIP STYLE	RECM. FASTENER	WEIGHT lbs./100 pcs. (g)
	MIN. in (mm)	MAX. in (mm)											
BC1M-S4	.06 (1.5)	0.90 (23)	.046 (1.2)	.095 (2.4)	.122 (3.1)	.156 (4.0)	.234 (5.9)	4.6 (117)	18 (80)	MINIATURE	CURVED	#4 (M2.5) SCREW	.08 (36)
BC2M-S4	.06 (1.5)	2.00 (51)	.046 (1.2)	.095 (2.4)	.122 (3.1)	.156 (4.0)	.234 (5.9)	8.3 (211)	18 (80)	MINIATURE	CURVED	#4 (M2.5) SCREW	.14 (64)
BC1.5I-S8	.03 (0.8)	1.5 (38)	.041 (1.0)	.141 (3.6)	.174 (4.4)	.166 (4.2)	.330 (8.4)	6.6 (168)	40 (178)	INTERMEDIATE	CURVED	#8 (M4) SCREW	.16 (73)

**Notes:**

1. SEE [www.panduit.com](http://www.panduit.com) FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE, PART MATERIAL, PART COLOR AND ANY THIRD PARTY RECOGNITION OR COMPLIANCE.

TITLE				<b>DOME-TOP Barb Ty LOCKING CLAMP TIE-BC SERIES</b>			
CUSTOMER DRAWING				BT-0070_SH1/AB			
DATASET FILE NAME				BT-0070_DC_SH1 of 2 r8A			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)							
.x ± - .xxx ± .020 [.5] .xx ± .02 [.51] ANGLES ± -							
THIRD ANGLE PROJECTION							
DRAWN BY		DATE		CHK		SCALE	
FKS		7-19-96		JVL		N/A	
MATERIAL:				NYLON 6.6 WITH 316 STAINLESS STEEL BARB			
DRAWING NUMBER:				BT-0070			
REV				SHT 1 OF 2			
DATE				SIZE			
BY				A			
CHK							
APR							
DESCRIPTION							
ECN							

B

A

NXGLOBAL\_ASIZE