



Pass and Seymour
20A 250V Heavy Duty Spec-Grade Single Receptacle, Back and Side Wire, Brown
Part No. 5871

Heavy-Duty Spec Grade Single Receptacle Back and Side Wire 20A 250V



Features & Benefits

| | |
|---|--|
| Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly. | One-piece heat-treated triple-wipe brass power contacts. |
| Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring. | Impact-resistant nylon face and thermoplastic back body. |
| Internal screw-pressure-plate back wire capable of accepting #14 - #10 AWG solid or stranded copper or copper-clad wire. | Terminal compartments isolated from each other for positive conductor containment. |
| Auto-ground clip assures positive ground. | For covering patents, see www.legrand.us/patents . |
| For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here . | Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact |

Specifications

General Info

| | | | |
|-----------------------|----------------|--------------------|--|
| Product Line | Pass & Seymour | Color | Brown |
| UPC Number | 785007587104 | Country Of Origin | Mexico |
| Number of Receptacles | 1 | Features | Single Piece Plated Steel Mounting Strap |
| Outlet Type | Straight Blade | Application Sector | Commercial |
| Wall Plate Included | No | Standard | UL498, CSA C22.2 No. 42, FEDSPEC |

| | | | |
|---------------------------------------|--------------------------|-------------------------|---------------|
| Warranty Type | 1-Year Limited Warranty | | |
| Dimensions | | | |
| Product Width US | 1.32 in | Product Depth US | 1.093 in |
| Product Height US | 1.68 in | | |
| Listing Agencies / 3rd Party Agencies | | | |
| cUL ListingNumber | 140596 | cULus Listed | Yes |
| cUL Listed | Yes | | |
| Technical Information | | | |
| Dielectric Strength | Withstands 2000V minimum | Connection Location | Back and Side |
| Number of Wires | 3 | Amperage | 20 A |
| Number of Poles | Double Pole | Wire Size | 14 - 10 AWG |
| Indoor/Outdoor | Indoor | NEMA Configuration Code | 6-20R |
| Wire Connection Type | Screw Terminals | Voltage | 250.0 V |
| Environmental Conditions | Flammability: UL94 V2 | | |