


Double-Pole, Double-Throw Manual Control Switch, 30A, 120/277V.



## Features & Benefits

Oversize silver alloy contacts for long life and better heat dissipation.

Side wired terminals accept #14 - #10 AWG copper or copper-clad conductors.

Fiber terminal insulation barriers standard.

Can be mounted in standard device boxes or in NEMA 1 sheet steel enclosures.

Bodies, covers, and toggles molded of durable nylon.

Single Pole-Double Throw and Double Pole-Double Throw.

Locking Switches supplied with one 1498-NT key.

Normally open.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

## Specifications

### General Info

|                     |                |                    |                        |
|---------------------|----------------|--------------------|------------------------|
| Product Line        | Pass & Seymour | Color              | Brown                  |
| Finish              | Matte          | UPC Number         | 785007125603           |
| Country Of Origin   | Mexico         | Material           | Thermoplastic          |
| Features            | Durable        | Switch Type        | Toggle                 |
| Number of Switches  | 1              | Application Sector | Commercial, Industrial |
| Wall Plate Included | No             | Standard           | UL Listed              |

|                                       |                                                                |                       |                   |
|---------------------------------------|----------------------------------------------------------------|-----------------------|-------------------|
| Warranty Type                         | 1-Year Limited Warranty                                        | Type                  | Manual Controller |
| Dimensions                            |                                                                |                       |                   |
| Product Width US                      | 1.5 in                                                         | Product Depth US      | 1.469 in          |
| Product Height US                     | 3.281 in                                                       |                       |                   |
| Listing Agencies / 3rd Party Agencies |                                                                |                       |                   |
| CSA Listed                            | Yes                                                            | cULus Listed          | Yes               |
| CSA File Number                       | 17949                                                          |                       |                   |
| Technical Information                 |                                                                |                       |                   |
| Load Rating                           | 30 A @ 120/277 VAC                                             | Connection Location   | Side Only         |
| Terminal Accommodation                | #14 AWG - #10 AWG                                              | Number of Gangs       | 1                 |
| Throw Type                            | Double Throw                                                   | Amperage              | 30 A              |
| Number of Poles                       | Double Pole, Single Pole                                       | Requires Neutral Wire | Yes               |
| Indoor/Outdoor                        | Indoor                                                         | Mounting Type         | Wall Box          |
| Wire Connection Type                  | Screw Terminals                                                | Voltage               | 120 VAC, 277 VAC  |
| Load Type                             | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |                       |                   |