



Pressure Sensitive Door and Canopy Switch 15A 120VAC, 15A 250VAC

## Features & Benefits

Easily accessible break-off separate or common feed.

Long-life red neon lamp in pilot light rated 1/25 Watt, 125V.

Side wire #12 and #14 AWG.

Two devices fit into the space of one.

Grounding combination devices meet NEC Requirements. Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

Product Line	Pass & Seymour	Color	White
Finish	Matte	UPC Number	785007120011
Country Of Origin	Mexico	Material	Thermoplastic
Features	Pressure Sensitive Switch	Switch Type	Canopy
Number of Switches	1	Application Sector	Commercial, Residential
Wall Plate Included	No	Standard	UL Listed
Warranty Type	1-Year Limited Warranty	Type	Switch

### Dimensions

---

Product Width US	1.516 in	Product Depth US	1.344 in
------------------	----------	------------------	----------

---

Product Height US	4.031 in
-------------------	----------

---

### Technical Information

---

Load Rating	15 A @ 120/250 VAC	Contact Configuration	N-0
-------------	--------------------	-----------------------	-----

---

Operating Cycles	30000	Connection Location	Side Only
------------------	-------	---------------------	-----------

---

Terminal Accommodation	#14 AWG - #12 AWG	Number of Gangs	1
------------------------	-------------------	-----------------	---

---

Throw Type	Single Throw	Amperage	15 A
------------	--------------	----------	------

---

Number of Poles	Single Pole	Requires Neutral Wire	Yes
-----------------	-------------	-----------------------	-----

---

Indoor/Outdoor	Indoor	Mounting Type	Wall Box
----------------	--------	---------------	----------

---

Wire Connection Type	Wire Terminal	Voltage	120 VAC, 250 VAC
----------------------	---------------	---------	------------------

---

Load Type	CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon	Environmental Conditions	Flammability: UL94 V2
-----------	---	--------------------------	--------------------------

---