Pass and Seymour

User Attachable In-Line Portable GFCI, 15A, Tri-cord connector, Manual Reset, Black

Part No. 1597FTC2MBK



The 15A field-wireable portable in-line GFCI with tri-cord connector conveniently provides GFCI protection when not present at the outlet. The rugged outdoor rated design makes it the ideal solution for providing reliable GFCI protection in temporary power applications including power tools, high-pressure power washers, wet vacuums, grounds-keeping equipment, spas and hot tubs, vending machines, portable signs and more.. The included tri-cord connector can accommodate up to three loads.

Features & Benefits

- Field wireable, portable, in-line GFCI designed for use across a variety of temporary power applications
- Includes an indicator light that illuminates when power is available
- Rugged polycarbonate housing is designed to withstand impact and hard use
- Manual reset
- Tri-cord connector accommodates up to three loads
- Self tests every three seconds to ensure the device is ready to protect
- Includes SafeLock protection. If critical components are damaged and ground fault protection is lost, power to the connected device is cut
- Open neutral protection automatically cuts power to the hot conductor if there's a loss in continuity in the neutral conductor leading to the device
- Rated for outdoor use

Specifications

General Info

Product Line	Pass & Seymour	Color	Black
Finish	Matte	UPC Number	785007450736
Country Of Origin	China	Features	Manual Reset, Portable GFCI, User Attachable
Outlet Type	GFCI, Outdoor	Application Sector	Commercial, Multi-Dwelling Unit, Residential
Wall Plate Included	No	Standard	UL943
Warranty Type	1-Year Limited Warranty		

Dimensions

Product Width US	2.0 in	Product Weight US	0.93 lb
Product Depth US	1.75 in	Product Height US	31.25 in
Product Length US	31.25 in		

Listing Agencies / 3rd Party Agencies

cULus Listed	Yes

Additional Information

RoHS Compliant	Yes	Energy Savings	No

Technical Information

Operating Temperature Min	-35 °C	Temperature Rise	Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current
Connection Location	Bottom	Frequency Rating	60 Hz
Trip Range	5±1 mA	Number of Wires	3
Operating Temperature Max	66 °C	Amperage	15 A
Number of Poles	Double Pole	Wire Size	14 - 12 AWG
Indoor/Outdoor	Outdoor	NEMA Configuration Code	5-15R
Operating Temperature	-35°-66°C	Wire Connection Type	Screw Terminal
Voltage	125.0 V		