

Pass and Seymour PlugTail® Connectors, Right Angle with IDEAL Connector, Solid, 6-inch Part No. PTRA6SOLBP



PlugTail® Connectors, Right Angle with IDEAL Connector, Solid, 6-inch. PlugTail® devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.

Features & Benefits

Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.

Pre-stripped connector leads fasten to conductors, easier than standard pigtails.

For covering patents, see www.legrand.us/patents.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

.036 inch thick, brass, triple-wipe power contacts for lasting retention.

Available in any wire length up to 25 inches, use Configurable Solutions to order.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.

PlugTail™ Connector: #12 AWG, THHN, copper conductor, 6" leads, stripped, solid, for use with PlugTail Receptacles only

Specifications

General Info

Product Line	Pass & Seymour	Color	Gray
Finish	Matte	UPC Number	785007278248
Country Of Origin	Mexico	Features	IDEAL Connector, Plug-In
Application Sector	Commercial	Standard	cULus UL498
Warranty Type	1-Year Limited Warranty	Туре	Accessory

Dimensions

Product Length US	6.0 in				
Listing Agencies / 3rd Party Agencies					
cULus ListingNumber	140596	cULus Listed	Yes		
Technical Information					
Dielectric Strength	Withstands 2000V minimum	Is Tamper-Resistant	Yes		
Connection Location	Back Only	Number of Wires	3		
Wire Size	12 AWG	Indoor/Outdoor	Indoor		
Wire Connection Type	PlugTail				