

Specifications



Photo is representative



Eaton R5A3025UBP336

Eaton rotary disconnect switch, Bulk pack of 336, 25 A, Non-fusible, Rotary handle, Three-pole, Rotary switch, R5 Series, 600 V

General specifications

PRODUCT NAME	Eaton rotary disconnect switch
CATALOG NUMBER	R5A3025UBP336
UPC	786685474021
PRODUCT LENGTH/DEPTH	2.57 in
PRODUCT HEIGHT	3.35 in
PRODUCT WIDTH	1.77 in
PRODUCT WEIGHT	0.51 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	CCC Marked
CERTIFICATIONS	UL 508 EN Listed CSA Certified IEC Rated
CATALOG NOTES	Suitable as motor disconnect



Powering Business Worldwide

Physical Attributes

NUMBER OF POLES	Three-pole
SERIES	R5

Miscellaneous

PRODUCT CATEGORY	Rotary Switch
------------------	---------------

Performance Ratings

AMPERAGE RATING	25A
VOLTAGE RATING	600 V

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
MULTIMEDIA	Switching Devices Flex Center
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - R5A3025UBP336
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.