

Specifications



Photo is representative



Eaton XTOB125LC1

Eaton XT IEC bimetallic overload relay, 95-125A overload range, 140 mm Frame size, 1NO-1NC contact configuration, used with 185-250A, 10A trip type

General specifications

PRODUCT NAME	Eaton XT IEC bimetallic overload relay
CATALOG NUMBER	XTOB125LC1
EAN	4015082100728
PRODUCT LENGTH/DEPTH	5.67 in
PRODUCT HEIGHT	6.65 in
PRODUCT WIDTH	5.04 in
PRODUCT WEIGHT	5.5 lb
COMPLIANCES	CE Marked RoHS Compliant ATEX Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947



Powering Business Worldwide

Product specifications

OVERLOAD RANGE	95-125 A
FRAME SIZE	140 mm

Resources

BROCHURES	C440 Electronic Overload Relay
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOB125LC1

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.