



Accepts front-loading TracJack modules and includes two snap-in label fields. Available in 1, 2, 3, 4 gangs. In addition to the Plastic TracJack Faceplate, Legrand offers a full range of TracJack faceplates in stainless steel, with a variety of port capacities to match your workstation applications. All TracJack plates offer recessed label fields.

Features & Benefits

Low profile design: Blends with most environments.

Easily accepts snap-in TracJacks: Easily field configured.

Textured finish: Hides future scuffs.

Compatible with all Tracjack adapters and connectors, including shielded

Recessed label fields: Supports TIA/EIA 606 standard.

Front-load module approach: Improves access for future work.

Oval mounting holes: Assists proper alignment

Specifications

General Info

Product Line	Ortronics	Color	Electrical Ivory
--------------	-----------	-------	------------------

Finish	Smooth	UPC Number	662875294245
--------	--------	------------	--------------

Country Of Origin	Taiwan, Province Of China	Material	Plastic
-------------------	---------------------------	----------	---------

Features	Front Loading, Label Field	Included	Label Field, Mounting Hardware
----------	----------------------------	----------	--------------------------------

Wall Plate Type	Networking	Application Sector	Commercial
-----------------	------------	--------------------	------------

Standard	UL Standard	Warranty Type	5-Year
----------	-------------	---------------	--------

Type	Workstation
------	-------------

Dimensions

Product Width US	2.74 in	Product Depth US	0.31 in
------------------	---------	------------------	---------

Product Height US	4.5 in
-------------------	--------

Additional Information

Product Environmental Profile	Yes
-------------------------------	-----

Technical Information

Operating Temperature Min	-10 °C	Compatibility	TracJack
---------------------------	--------	---------------	----------

Number of Ports	2	Operating Temperature Max	60 °C
-----------------	---	---------------------------	-------

Number of Gangs	1	Indoor/Outdoor	Indoor
-----------------	---	----------------	--------

Mounting Type	Box Mounted	Operating Temperature	-10°-60°C
---------------	-------------	-----------------------	-----------

Orientation	Vertical
-------------	----------
