

Specifications



Photo is representative

Eaton T48M11S6716CU

Eaton General purpose ventilated transformer, DS-3 (1-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 120/240V, 150°C rise, 167 kVA, 16, Copper windings

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	T48M11S6716CU
UPC	786680210525
PRODUCT LENGTH/DEPTH	33.97 in
PRODUCT HEIGHT	62.91 in
PRODUCT WIDTH	29.97 in
PRODUCT WEIGHT	1665 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEMA TP-1 Compliant
CERTIFICATIONS	UL Listed
CATALOG NOTES	NEMA TP-1 efficient, Grade 316 stainless steel enclosure (does not imply NEMA 4X rating.)



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Copper
FRAME	814E
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous

WEATHERSHIELD	WS13S
----------------------	-------

Performance Ratings

FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	120/240 V
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	167 kVA

Resources

	Eaton's high-efficiency dry-type transformers
BROCHURES	Eaton's low-voltage dry-type distribution transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - T48M11S6716CU

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.