

# Specifications



Photo is representative

## Eaton V29M48T4516

Eaton General purpose ventilated transformer, Aluminum windings, NEMA 2, 60 Hz, 220°C, 45 kVA, Floor or wall, upright only , Three-phase, 208 Delta V, 480 Delta Vac, NEMA ST-20, 150°C, 45 kVA, 208 Vac-480 Vac, DOE 2016

### General specifications

<b>PRODUCT NAME</b>	Eaton General purpose ventilated transformer
<b>CATALOG NUMBER</b>	V29M48T4516
<b>UPC</b>	786680204937
<b>PRODUCT LENGTH/DEPTH</b>	21.13 in
<b>PRODUCT HEIGHT</b>	36.88 in
<b>PRODUCT WIDTH</b>	24.88 in
<b>PRODUCT WEIGHT</b>	433 lb
<b>WARRANTY</b>	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>COMPLIANCES</b>	DOE2016 Efficient
<b>CERTIFICATIONS</b>	UL Listed
<b>CATALOG NOTES</b>	10 CFR Part 431 (2016) Efficient



Powering Business Worldwide

## Physical Attributes

<b>COIL MATERIAL</b>	Aluminum
<b>ENCLOSURE</b>	NEMA 2
<b>INSULATION</b>	220 °C
<b>MOUNTING</b>	Floor or wall, upright only
<b>TAP SIZE</b>	2 at +2.5%, 4 at -2.5%
<b>TYPE</b>	Energy-efficient ventilated type DT-3 transformer

## Performance Ratings

<b>EFFICIENCY</b>	10 CFR Part 431-2016 (DOE 2016)
<b>FREQUENCY RATING</b>	60 Hz
<b>KVA RATING</b>	45 kVA
<b>PRIMARY VOLTAGE</b>	208 V
<b>SECONDARY VOLTAGE</b>	480 V
<b>SOUND LEVEL</b>	NEMA ST-20
<b>TEMPERATURE RISE</b>	150 °C rise
<b>VOLT AMPERE RATING</b>	45 kVA
<b>VOLTAGE RATING</b>	208 Vac-480 Vac

## Resources

	<a href="#">Eaton's high-efficiency dry-type transformers</a>
<b>BROCHURES</b>	<a href="#">Eaton's low-voltage dry-type distribution transformers</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - V29M48T4516</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.