

Specifications



Photo is representative

Eaton XDT1A5X

Eaton Crouse-Hinds series XDT dry-type transformer, 60 Hz, 5 kVA, 316 stainless steel, Single-phase, 480 Vac, 120/240 Vac, Copper windings, Resin encapsulated

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series XDT dry-type transformer
CATALOG NUMBER	XDT1A5X
UPC	662276445093
PRODUCT LENGTH/DEPTH	13.9 in
PRODUCT HEIGHT	14.8 in
PRODUCT WIDTH	9.5 in
PRODUCT WEIGHT	130 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 2
NEMA RATING	4X

Resources

3D MODELS	SP3D Design Package - XDT and XTT Hazardous Area Transformers
BROCHURES	XDT and XTT Hazardous Area Transformers Flyer
CATALOGS	XDT and XTT Hazardous Area Transformers catalog page
CERTIFICATION REPORTS	XDT and XTT Hazardous Area Transformers UL certification XDT and XTT Hazardous Area Transformers Canadian certification
INSTALLATION INSTRUCTIONS	IF XDT - XDT Series Hazardous Area Transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XDT1A5X XDT Hazardous Area Transformers

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Product specifications

TYPE	Resin encapsulated
PHASE	Single-phase
PRIMARY VOLTAGE	480 Vac
SECONDARY VOLTAGE	120 Vac/240 Vac
FREQUENCY RATING	60 Hz
MATERIAL	316 stainless steel
SPECIAL FEATURES	Copper windings



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.