

# Specifications



Photo is representative

## Eaton XDT3B30X

Eaton Crouse-Hinds series XDT dry-type transformer, 60 Hz, 30 kVA, 316 stainless steel, Three-phase, 480 Vac, 208Y/120 Vac, Copper windings, Resin encapsulated

### General specifications

<b>PRODUCT NAME</b>	Eaton Crouse-Hinds series XDT dry-type transformer
<b>CATALOG NUMBER</b>	XDT3B30X
<b>UPC</b>	662276423909
<b>PRODUCT LENGTH/DEPTH</b>	25.18 in
<b>PRODUCT HEIGHT</b>	27.28 in
<b>PRODUCT WIDTH</b>	12.69 in
<b>PRODUCT WEIGHT</b>	620 lb



Powering Business Worldwide

## Certifications and compliances

<b>AREA CLASSIFICATION</b>	Hazardous/Classified Locations
<b>STANDARDS TYPE</b>	NEC/CEC
<b>NEC HAZARDOUS RATING</b>	Class I, Division 2
<b>NEMA RATING</b>	4X

## Resources

3D MODELS	<a href="#">SP3D Design Package - XDT and XTT Hazardous Area Transformers</a>
BROCHURES	<a href="#">XDT and XTT Hazardous Area Transformers Flyer</a>
CATALOGS	<a href="#">XDT and XTT Hazardous Area Transformers catalog page</a>
CERTIFICATION REPORTS	<a href="#">XDT and XTT Hazardous Area Transformers Canadian certification</a> <a href="#">XDT and XTT Hazardous Area Transformers UL certification</a>
INSTALLATION INSTRUCTIONS	<a href="#">IF XDT - XDT Series Hazardous Area Transformers</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">XDT Hazardous Area Transformers</a> <a href="#">Eaton Specification Sheet - XDT3B30X</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

## Product specifications

<b>TYPE</b>	Resin encapsulated
<b>PHASE</b>	Three-phase
<b>PRIMARY VOLTAGE</b>	480 Vac
<b>SECONDARY VOLTAGE</b>	208Y/120 Vac
<b>FREQUENCY RATING</b>	60 Hz
<b>MATERIAL</b>	316 stainless steel
<b>SPECIAL FEATURES</b>	Copper windings



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.