

Specifications



Photo is representative

Eaton XDT3B45X

Eaton Crouse-Hinds series XDT dry-type transformer, 60 Hz, 45 kVA, 316 stainless steel, Three-phase, 480 Vac, 208Y/120 Vac, Copper windings, Resin encapsulated

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series XDT dry-type transformer
CATALOG NUMBER	XDT3B45X
UPC	662276424654
PRODUCT LENGTH/DEPTH	28 in
PRODUCT HEIGHT	27.5 in
PRODUCT WIDTH	15.03 in
PRODUCT WEIGHT	811 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 2
NEMA RATING	4X

Resources

3D MODELS	SP3D Design Package - XDT and XTT Hazardous Area Transformers
BROCHURES	XDT and XTT Hazardous Area Transformers Flyer
CATALOGS	XDT and XTT Hazardous Area Transformers catalog page
CERTIFICATION REPORTS	XDT and XTT Hazardous Area Transformers UL certification XDT and XTT Hazardous Area Transformers Canadian certification
INSTALLATION INSTRUCTIONS	IF XDT - XDT Series Hazardous Area Transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XDT3B45X XDT Hazardous Area Transformers

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Product specifications

TYPE	Resin encapsulated
PHASE	Three-phase
PRIMARY VOLTAGE	480 Vac
SECONDARY VOLTAGE	208Y/120 Vac
FREQUENCY RATING	60 Hz
MATERIAL	316 stainless steel
SPECIAL FEATURES	Copper windings



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.