



Color: Bronze

Weight: 7.1 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant	Watts	30/25/20/15W
120V	N/A	Color Temp	3000/4000/5000K
208V	N/A	Color Accuracy	83-86 CRI
240V	N/A	L70 Lifespan	100,000 Hours
277V	N/A	Lumens	1,964-4,544 lm
Input Watts	14.3-31.3W	Efficacy	133.6-150.9 lm/W

**Technical Specifications**

**Field Adjustability**

**Optical Field Adjustability:**

45°, 30°, 15° and 0° (factory default 0°)

**Field Adjustable:**

Field Adjustable Light Output:

30W/25W/20W/15W (factory default 30W)

Color Temperature Selectable:

3000K, 4000K and 5000K (factory default 4000K)

**Performance**

**Lifespan:**

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Wattage Equivalency:**

30W: Replaces up to 175W Metal Halide (MH) or 150W High Pressure Sodium (HPS)

25W: Replaces up to 175W Metal Halide (MH) or 150W High Pressure Sodium (HPS)

20W: Replaces up to 125W Metal Halide (MH) or 100W High Pressure Sodium (HPS)

15W: Replaces up to 100W Metal Halide (MH) or 70W High Pressure Sodium (HPS)

**LED Characteristics**

**LEDs:**

Edge-lit long-life, high-efficiency, surface-mount LEDs; binned and mixed for uniform light output and color.

**Electrical**

**Driver:**

30W: Class 2, Constant Current, 480V, 50/60 Hz, 480V: 0.077A

25W: Class 2, Constant Current, 480V, 50/60 Hz, 480V: 0.065A

20W: Class 2, Constant Current, 480V, 50/60 Hz, 480V: 0.06A

15W: Class 2, Constant Current, 480V, 50/60 Hz, 480V: 0.045A

**Dimming Driver:**

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

**THD:**

30W: 14.76% at 480V

25W: 15.94% at 480V

20W: 35.33% at 480V

15W: 58.72% at 480V

**Power Factor:**

30W: 91.2% at 480V

25W: 88.3% at 480V

20W: 84.8% at 480V

15W: 68.1% at 480V

**Aux Power Supply:**

Yes

**Dim to Off:**

Yes

**Photocell:**

480V selectable photocell that can be turned on and off.

**Surge Protection:**

DM(L/N): 6KV, CM(L/N-PE): 6KV

**Construction**

**Cold Weather Starting:**

The minimum starting temperature is -40°C (-40°F)

**Maximum Ambient Temperature:**

Suitable for use in up to 40°C (104°F)

**Housing:**

Die-cast aluminum

**Lens:**

Polycarbonate lens

**Gaskets:**

High-temperature silicone

**Finish:**

Formulated for high durability and long-lasting color

## Technical Specifications (continued)

### Green Technology:

Mercury and UV free. RoHS-compliant components.

### Compliance

---

#### UL Listed:

Suitable for wet locations

#### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

#### IP Rating:

Ingress protection rating of IP65 for dust and water

#### DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

DLC Product Code: S-LCJCTC

### Installation

---

#### Mounting:

Hinged wiring access and conduit entries on the back, sides, top and bottom make installation a snap

### Optical

---

#### BUG Rating:

30W: B2 U0 G1

25W: B2 U0 G1

20W: B2 U0 G1

15W: B1 U0 G1


### Other

---

#### 5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Dimensions**



**Features**

- DLC Premium listed
- 0-10V dimming standard
- 100,000-hour LED Life
- 5-Year, limited warranty

**Ordering Matrix**

Family	Housing Size	Wattage	Color Temp	Finish	Forward Throw	Driver	Options	
SLIM22	-	S	-	30			/480	
	S = Small M = Medium L = Large	30 = 30/25/20/15W 60 = 60/50/40/30W 100 = 100/85/70/50W 150 = 150/125/100/75W	Blank = 3000/4000/5000K CCT Adjustable	Blank = Bronze W = White	Blank = Adjustable Throw 0°/15°/30°/45°	Blank = 120-277V, 0-10V /480 = 480V, 0-10V Dimming	Blank = Selectable Photocell /E = Selectable Photocell w/Battery Backup	