

Power Protection Devices, Receptacle, Self Test, GFCI, WR, Commercial Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Black

By Hubbell Wiring Device-Kellems

Catalog # [GFRWR20BLK](#)

Power Protection Devices, Receptacle, Self Test, GFCI, WR, Commercial Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Black



Features

- Patented AUTOGUARD® self test technology
- Meets NEC requirements for weather resistance (406.9), UV and corrosion resistance for harsh and damp applications
- Single LED status indicator - green indicates power, red indicates a trip, flashing red indicates end of life

General

Catalog Number	GFRWR20BLK
Color	Black
EU RoHS Indicator	Contact Manufacturer
Series	Heavy Duty
Specifications	<ul style="list-style-type: none">• Base - Nylon• Face - Nylon• Ground Contacts - Brass• Mounting Screws - Zinc plated steel• Mounting Strap - Zinc plated steel• Power Contacts - Brass
Style	Standard
Type	Weather Resistant
UPC	883778999772

Electrical Ratings

Current / Amperage Rating	20 A
Voltage Rating Description	125 V

Certifications And Compliance

Industry Standard(s)	Meets All NEC® Requirements
Nema Rating	5-20R

Logistics

Carton Quantity	10
-----------------	----

Product Assets

Catalog Page - WDK K-8 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - M-14627 AutoCAD Drawing
Installation Manuals - PD2987
Literature - Commercial GFCI Receptacles
Literature - FREQUENTLY ASKED QUESTIONS Commercial GFCI Receptacles
Sales Drawings - M14627
Specifications - WIRING_GFRWR20BLK_spec