

Specifications



Photo is representative



Eaton V48M28B75CUEELS47

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 80°C rise, 75 kVA, Copper windings, EE, LS47

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	V48M28B75CUEELS47
UPC	786680033551
PRODUCT LENGTH/DEPTH	23.42 in
PRODUCT HEIGHT	48.56 in
PRODUCT WIDTH	28.22 in
PRODUCT WEIGHT	840 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEMA TP-1 Compliant
CERTIFICATIONS	UL Listed
CATALOG NOTES	NEMA TP-1 efficient, Low sound equal to 47 dB



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Copper
FRAME	916A
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous

MODIFICATION 1	Low sound 47 dB
WEATHERSHIELD	WS19

Performance Ratings

FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	208 Y/120 V
TEMPERATURE RISE	80 °C rise
VOLT AMPERE RATING	75 kVA

Resources

CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - V48M28B75CUEELS47

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.