

Specifications



Eaton XTM CXFC22

Miniature Contactor Accessory - Auxiliary Contact, Four-pole, Spring cage terminals, 2NO-2NC contact configuration, 10A conventional thermal rating, Front mounting, used with XTRM miniature control relays

General specifications

PRODUCT NAME	Eaton motor control auxiliary contact
CATALOG NUMBER	XTMCXFC22
EAN	4015080101123
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	1.26 in
PRODUCT WIDTH	1.77 in
PRODUCT WEIGHT	0.09 lb
WARRANTY	Not Applicable
COMPLIANCES	ATEX Compliant CE Marked CCC Marked
CERTIFICATIONS	IEC 60947 EN 60947 UL Listed CSA Certified
CATALOG NOTES	Orders must be placed in multiples of package quantity listed.
GLOBAL CATALOG	XTMCXFC22

Product specifications

USED WITH	XTRM miniature control relays
NUMBER OF POLES	Four-pole
TYPE	Miniature Contactor Accessory - Auxiliary Contact
TERMINALS	Spring cage
CONTACT CONFIGURATION	2 NO-2 NC
MOUNTING METHOD	Front
SPECIAL FEATURES	Used with XTRM miniature control relays
CONVENTIONAL THERMAL CURRENT	10A
QUANTITY	5

Resources

CATALOGS

[Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTMCF22](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

