

Specifications



Photo is representative



Eaton V29R47B12CUEE

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 208V, Taps: 1 at +5%/2 at -5%, SV 480Y/277V, 80°C rise, 112.5 kVA, Copper windings, EE

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	V29R47B12CUEE
UPC	786680094781
PRODUCT LENGTH/DEPTH	23.42 in
PRODUCT HEIGHT	48.56 in
PRODUCT WIDTH	28.22 in
PRODUCT WEIGHT	1177 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEMA TP-1 Compliant
CERTIFICATIONS	UL Listed
CATALOG NOTES	NEMA TP-1 efficient

Physical Attributes

COIL MATERIAL	Copper
FRAME	916A
TAP SIZE	1 at +5% FCAN, 2 at -5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous

WEATHERSHIELD	WS19
---------------	------

Performance Ratings

FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	208 V
SECONDARY VOLTAGE	480 Y/277 V
TEMPERATURE RISE	80 °C rise
VOLT AMPERE RATING	112.5 kVA

Resources

CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - V29R47B12CUEE

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

