

Specifications



Photo is representative



Eaton T39M11S45X

General-Purpose Transformer, Ventilated, Dry Type Distribution, DS-3, Single-phase, PV: 400V, Taps: 2 at +2.5% FCAN, 4 at -2.5% FCBN, SV: 120/240V, 150°C, 45 kVA, Al windings, Frame: 818, uses WS11

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	T39M11S45X
UPC	786680065194
PRODUCT LENGTH/DEPTH	20.36 in
PRODUCT HEIGHT	37.59 in
PRODUCT WIDTH	22.89 in
PRODUCT WEIGHT	366 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Aluminum
DESIGN	DS-3
FRAME	818
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous

WEATHERSHIELD	WS11
----------------------	------

Performance Ratings

FREQUENCY RATING	50-60 Hz
KVA RATING	45 kVA
PRIMARY VOLTAGE	400 V
SECONDARY VOLTAGE	120/240 V
TEMPERATURE RISE	150 °C rise

Resources

CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - T39M11S45X

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.