Specifications



Photo is representative

Eaton V48M22F33EE

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 240 delta/120 midtap, 115°C rise, 300 kVA, EE

General specifications	
PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	V48M22F33EE
UPC	786680050206
PRODUCT LENGTH/DEPTH	32.65 in
PRODUCT HEIGHT	57.54 in
PRODUCT WIDTH	36.69 in
PRODUCT WEIGHT	1795 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEMA TP-1 Compliant
CERTIFICATIONS	UL Listed
CATALOG NOTES	NEMA TP-1 efficient

Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Aluminum
FRAME	923
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Performance Ratings

FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	240 delta/120 midtap
TEMPERATURE RISE	115 °C rise
VOLT AMPERE RATING	300 kVA

Miscellaneous

WEATHERSHIELD	WS37

Resources

CATALOGS	Commercial Distribution, Transformers, Volume 2, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - V48M22F33EE

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.