

Specifications



Eaton C10G0.5

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 0.5 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder

General specifications

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C10G0.5
MODEL CODE	CYLINDRICAL FUSE 10 x 38 0-5A GG 500V AC
UPC	051712589871
EAN	5027590493376
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	7.7 g
WARRANTY	1 year limited
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	IEC 60269
GLOBAL CATALOG	C10G0.5



Powering Business Worldwide

Product specifications

AMPERAGE RATING	0.5 A
FUSE SIZE	10 x 38 mm
CURRENT TYPE	AC
BREAKING CAPACITY	120 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	500 V
CLASS	Class C gL/gG
FUSE TYPE	C10G
UTILIZATION CATEGORY	gG (cable protection/equipment protection)
FUSE INDICATOR	Other
WATT LOSSES	1.43 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	10 mm x 38 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CHM Modular fuse holder
MATERIAL	Ceramic
MOUNTING METHOD	Holder
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	500 V
TYPE	fuse
APPLICATION	<ul style="list-style-type: none">• for industrial applications• for general purpose use

Resources

	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CATALOGS	eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf Bussmann series complete full line catalog no. 1007
DECLARATIONS OF CONFORMITY	eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.