

Specifications



Photo is representative

Eaton FWJ-300A

Eaton Bussmann series FWJ high speed fuse, 300A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud

General specifications

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWJ-300A
UPC	051712796248
EAN	5027590021265
PRODUCT LENGTH/DEPTH	147 mm
PRODUCT HEIGHT	51 mm
PRODUCT WIDTH	51 mm
PRODUCT WEIGHT	527 g
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	CSA Certified UL Recognized
GLOBAL CATALOG	FWJ-300A



Powering Business Worldwide

Product specifications

AMPERAGE RATING	300 A
BREAKING CAPACITY	100 kA
FUSE INDICATOR	Non Indicating
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
RATED SWITCHING CAPACITY	100 A
RATED VOLTAGE AC	1000 V
RATED VOLTAGE DC	800 V
MOUNTING DIMENSION	Other
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	113.75 mm
CURRENT TYPE	AC/DC
CLASS	Class aR
CLEARING (I2T)	164000 at 1000 V
WATT LOSSES	56 W
FUSE SHAPE	Center bolted tags
PRE ARC (I2T)	23500
COLOR	None
INTERRUPT RATING	450-600A) 25 kAIC (35-200A) 100 kAIC (250-2000A) 50 kAIC at 800 Vdc (35-200A
CONNECTION	Blade end x blade end
CONSTRUCTION SIZE	Other
MOUNTING METHOD	Stud
PACKAGING TYPE	Standard
VOLTAGE RATING	1000 V
TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
FUSE TYPE	FWJ-A
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

Resources

CATALOGS

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

MCAD MODEL

[eaton-hs-round-body-fuses-mcad-3d-models-fwj-250-400a.stp](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

