



Clarity 6 angled 48-port high density Category 6 patch panel utilizes an innovative recessed angle design for a lower mounted profile. This Clarity 6 patch panel is component compliant to TIA/EIA Category 6 performance requirements. It occupies one rack unit, and measures 19" x 3.5". Jacks are grouped in six-port modules. It is part of the Clarity 6 link and channel solution that provides significant installed performance headroom.

Features & Benefits

Recessed design with lower mounted profile: Directs cords more easily to vertical management.

Center tuned to Clarity 6 patch cords: More transparent mated union.

Easy lace 110 termination: Saves installation time.

High density design: Maximizes rack utilization.

ETL verified to TIA Category 6 component spec: Elevated component performance.

Universal wiring: Supports T568A and T568B installs.

Supplied rear cable management: Supports good cabling practice.

RoHS compliant: Lead free.

Specifications

General Info

Product Line	Ortronics	Color	Black
UPC Number	662875497226	Country Of Origin	Mexico
Material	Steel	Application Sector	Commercial, Industrial
Standard	RoHS	Warranty Type	5-Year
Type	Panel		

Dimensions

Product Width US	19.0 in	Product Depth US	6.1 in
Product Height US	3.5 in		

Additional Information

RoHS Compliant	Yes	Product Environmental Profile	Yes
----------------	-----	-------------------------------	-----

Technical Information

Category Performance Application	Cat6	Compatibility	HDJ
Rack Units	1 U	Wire Gauge	22-24 AWG
Number of Ports	48	Shielded/Unshielded Cable	Shielded
Connector Type	RJ-45	Wattage	100 W
Voltage	60.0 V		
