Eaton C22G40S

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 40 Amps, 80 kA Breaking capacity, class gG/gL, with striker, compatible with a CH22 Modular fuse holder

General specifications	
PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C22G40S
UPC	051712668491
EAN	5027590495455
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	22 mm
PRODUCT WIDTH	22 mm
PRODUCT WEIGHT	51.4 g
WARRANTY	1 year limited
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	IEC 60269
GLOBAL CATALOG	C22G40S

EAT•N

Powering Business Worldwide

Product specifications

AMPERAGE RATING	40 A
FITTED WITH:	Striker
FUSE SIZE	22 x 58 mm
CURRENT TYPE	AC
BREAKING CAPACITY	80 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	690 V
CLASS	Class C gL/gG
FUSE TYPE	C22G
UTILIZATION CATEGORY	gG (cable protection/equipment protection)
FUSE INDICATOR	Top fuse status indicator
WATT LOSSES	4 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	22 mm x 58 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CH22 Modular fuse holder
MATERIAL	Ceramic
MOUNTING METHOD	22 x 58 mm CH Modular fuse holder
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	690 V
TYPE	Fuse
SPECIAL FEATURES	Striker
APPLICATION	• for industrial applications • for general purpose use

Resources

CATALOGS	[eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf](#) [eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#) [Bussmann series complete full line catalog no. 1007](#)
DECLARATIONS OF CONFORMITY	[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf](#) [eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf](#)
TECHNICAL DATA SHEETS	[720115 Cylindrical fuses](#)

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	