



circuit breaker VL150 UL type DG (cat no. HDK3T060L) non-interchangeable frame, with circuit breaker approval acc. to UL 489 high breaking capacity 3-pole; NEMA rating 65KA@480V and 18KA@600/347V (molded case circuit breaker) Electronic Trip Unit ETU, LSI TA=40°C In=60A, rated current ISD=1.5-10xIR, II=11xIN short-circuit protection Ir=30-60A Electronic Trip Unit for line protection with terminals feeder and load-side (line and load) without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.546 kg
Net Weight	2.546 kg

General Product Approval



[Confirmation](#)



EMV Test Certificates Marine / Shipping



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



other Railway

[Confirmation](#)

[Miscellaneous](#)

[Special Test Certificate](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2506-2PE33-0AA0>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL2506-2PE33-0AA0>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2506-2PE33-0AA0
CAx-Online-Generator
<http://www.siemens.com/cax>
Information- and Downloadcenter (catalogues, leaflets,...)
<http://www.siemens.com/energy-automation>



last modified: 4/8/2025

