

Specifications

Eaton FWX-12A14F

Eaton Bussmann series FWX high speed fuse, 12A, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWX-12A14F
UPC	051712795562
EAN	5027590501330
PRODUCT LENGTH/DEPTH	55 mm
PRODUCT HEIGHT	32 mm
PRODUCT WIDTH	73 mm
PRODUCT WEIGHT	21.2 g
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
GLOBAL CATALOG	FWX-12A14F



Powering Business Worldwide

Product specifications

AMPERAGE RATING	1200 A
ACCESSORIES	<ul style="list-style-type: none">• CH14 Modular fuse holder• FW14-PCB
BREAKING CAPACITY	200 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
FUSE INDICATOR	Other
RELEASE CHARACTERISTIC	Other
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
FUSE SIZE	14 x 51 mm
RATED VOLTAGE AC	250 V
RATED VOLTAGE DC	250 V
CLASS	Class aR
FUSE SHAPE	Cylindrical
INTERRUPT RATING	200 kAIC
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	14 mm x 51 mm
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	700 V
TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
FUSE TYPE	FWX-A14F
BREAKING CAPACITY AT NOMINAL VOLTAGE, AC	200 kA
BREAKING CAPACITY AT NOMINAL VOLTAGE, DC	50 kA

Resources

CATALOGS	eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf Bussmann series complete full line catalog no. 1007
MCAD MODEL	eaton-hs-round-body-fuses-mcad-3d-models-fwx-5-30a-14f.stp

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

