

Specifications



Photo is representative



Eaton BK/GMC-2-R

Eaton GMC Series Medium time-delay fuse
2A, 250 Vac, 32 Vdc (self certified), BK-GMC-
2-R

General specifications

PRODUCT NAME	Eaton Bussmann series GMC time-delay fuse
CATALOG NUMBER	BK/GMC-2-R
UPC	051712642163
PRODUCT HEIGHT	20 mm
PRODUCT DIAMETER	5.2 mm
PRODUCT WEIGHT	0.7 g
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked



Powering Business Worldwide

Product specifications

USED WITH	out axial leads
AMPERAGE RATING	2 A
INTERRUPT RATING	10 kAIC at 125 Vac 100 AIC at 250 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	60 min at 135%, 2 min at 200%
MATERIAL	Glass tube Nickel-plated brass end cap construction
QUANTITY	100
VOLTAGE RATING	250 Vac, 32 Vdc (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton GMC medium time delay glass tube fuses data sheet](#)

[Eaton Specification Sheet - BK/GMC-2-R](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.