

Specifications



Photo is representative

Eaton XTCE115G00T

Eaton XT IEC contactor, 115A, 24 Vac, 50-60 Hz, 0NO-0NC, 115A, Frame G, 90 mm, 50-60 Hz, 10, 25, 25/ 40, 50, 100, 100 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing contactor

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE115G00T
EAN	4015082395452
PRODUCT LENGTH/DEPTH	6.2992126 in
PRODUCT HEIGHT	6.69291339 in
PRODUCT WIDTH	4.37007874 in
PRODUCT WEIGHT	0.5070632 lb
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

Product specifications

AMPERAGE RATING	115A
HP RATING - MAX	10, 25, 25/ 40, 50, 100, 100 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50-60 Hz
FRAME SIZE	90 mm
TERMINALS	Screw terminals
COIL VOLTAGE	24 Vac, 50-60 Hz
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	115 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE115G00T

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

