

Specifications



Photo is representative



Eaton XTCE185H22B

Eaton XT IEC contactor, 185A, 190 Vac 50 Hz, 240 Vac 60 Hz, 2NO-2NC, 185A, Frame H, 140 mm, 50-60 Hz, 50, 75, 150, 200 hp (3PH @200, 240, 480, 600 V), Three-pole, Non-reversing, , Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE185H22B
EAN	4015081363155
PRODUCT LENGTH/DEPTH	6.22047244 in
PRODUCT HEIGHT	7.08661417 in
PRODUCT WIDTH	5.51181102 in
PRODUCT WEIGHT	0.5070632 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

Product specifications

AMPERAGE RATING	185A
HP RATING - MAX	50, 75, 150, 200 hp (3PH @200,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50-60 Hz
FRAME SIZE	140 mm
TERMINALS	Screw terminals
COIL VOLTAGE	190-240 Vac, 50-60 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	185 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE185H22B

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.