

Specifications



Eaton XTMC6A01A

Eaton XT IEC contactor, 6.60A, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NC, 20A, 45 mm mini, 50-60 Hz, 0.25, 0.75, 1/ 1.5, 2, 3, 3 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	XTMC6A01A
EAN	4015080516361
PRODUCT LENGTH/DEPTH	2.5 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	2.5 in
PRODUCT WEIGHT	0.5 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

Product specifications

AMPERAGE RATING	6.60A
HP RATING - MAX	0.25, 0.75, 1/ 1.5, 2, 3, 3 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing mini contactor
FREQUENCY RATING	50-60 Hz
TERMINALS	Screw terminals
COIL VOLTAGE	110-120 Vac, 50/60 Hz
CONTACT CONFIGURATION	1 NC
CONTINUOUS AMPERE RATING	20 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	S1. E4. Ask the Experts - NEMA, IEC and DP contactors Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTMC6A01A
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

