

# Specifications

## Eaton 315NHG3B-690

Eaton Bussmann series low voltage NH Fuse, 315 A, 690 V, 120 kAIC, 22 Watt, Blade end

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series low voltage NH Fuse
<b>CATALOG NUMBER</b>	315NHG3B-690
<b>MODEL CODE</b>	NH FUSE 315A 690V gG SIZE 3
<b>UPC</b>	051712193023
<b>EAN</b>	5027590476539
<b>PRODUCT LENGTH/DEPTH</b>	150 mm
<b>PRODUCT HEIGHT</b>	86 mm
<b>PRODUCT WIDTH</b>	71 mm
<b>PRODUCT WEIGHT</b>	1110 g
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	RoHS Compliant CE Marked
<b>CERTIFICATIONS</b>	IEC 60269-1 IEC 60269-2 DIN 43620
<b>GLOBAL CATALOG</b>	315NHG3B-690



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	315 A
<b>FITTED WITH:</b>	Metal gripping lugs
<b>FUSE SIZE</b>	NH3
<b>CURRENT TYPE</b>	AC
<b>BREAKING CAPACITY</b>	120 kA
<b>FREQUENCY RATING - MAX</b>	62 Hz
<b>FREQUENCY RATING - MIN</b>	45 Hz
<b>RATED SWITCHING CAPACITY</b>	120 kA
<b>RATED VOLTAGE AC</b>	690 V
<b>CLASS</b>	Class gG/gL
<b>FUSE TYPE</b>	Square body with knife blade contact
<b>ACCESSORY/SPARE PART TYPE</b>	SDL-3 Solid link FEH- Fuse extraction handle SD3-SK Shroud kit SD3-PB 2-phase barriers and 2 ganging links TD3-IP20 Triple pole protection kit
<b>UTILIZATION CATEGORY</b>	gL/gG (cable protection/equipment protection)
<b>INTERRUPT RATING</b>	120 kAIC
<b>FUSE INDICATOR</b>	Combination fuse status indicator
<b>INSULATED METAL GRIPPING LUGS (IMGL)</b>	No
<b>WATT LOSSES</b>	22 W
<b>CONNECTION</b>	Blade end
<b>CONSTRUCTION</b>	NH3
<b>CONSTRUCTION SIZE</b>	NH3
<b>FUSE SHAPE</b>	Knife blade contacts Square body
<b>VOLTAGE TYPE</b>	AC
<b>SUITABLE FOR</b>	SD3-D Single pole NH Fuse base Microswitch 170H0235 EBH Size 00 to 4 Horizontal fuse switch-disconnectors TD3-D Triple pole NH Fuse base
<b>MATERIAL</b>	Ceramic body
<b>PACKAGING TYPE</b>	Standard

## Resources

	<a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>
	<a href="#">eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf</a>
CATALOGS	<a href="#">NH Fuse links, bases and gear</a> <a href="#">Bussmann series complete full line catalog no. 1007</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-low-voltage-nh-fuse-declaration-of-conformity-uk250961en.pdf</a> <a href="#">eaton-low-voltage-nh-fuse-declaration-of-conformity-eu250478en.pdf</a>
MCAD MODEL	<a href="#">eaton-iec-lv-fuses-mcad-3d-models-250-630a-nh-3b.stp</a>
MULTIMEDIA	<a href="#">Eaton Bussmann – NH fuse link portfolio</a>
PRESENTATIONS	<a href="#">NH Overview Video</a>

<b>QUANTITY</b>	3
<b>VOLTAGE RATING</b>	690 V
<b>TYPE</b>	Fuse
<b>SPECIAL FEATURES</b>	Live gripping lug
<b>APPLICATION</b>	<ul style="list-style-type: none"><li>• industrial</li><li>• Utilities, Solar, Wind</li></ul>
<b>RATED SWITCHING CAPACITY AC</b>	120 kA

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

