

Specifications



Eaton C10M2

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 2 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder

General specifications

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C10M2
MODEL CODE	CYLINDRICAL FUSE 10 x 38 2A AM 500V AC
UPC	051712754545
EAN	5027590493673
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	8.2 g
WARRANTY	1 year limited
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269
GLOBAL CATALOG	C10M2



Powering Business Worldwide

Product specifications

AMPERAGE RATING	2 A
FUSE SIZE	10 x 38 mm
CURRENT TYPE	AC
BREAKING CAPACITY	120 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	500 V
CLASS	Class aM
FUSE TYPE	C10M
UTILIZATION CATEGORY	aM (switchgear protection)
FUSE INDICATOR	Other
WATT LOSSES	0.18 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	10 mm x 38 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CHM Modular fuse holder
MATERIAL	Ceramic
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	500 V
TYPE	fuse

APPLICATION	<ul style="list-style-type: none">• motor protection• for industrial applications
-------------	--

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Resources

	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CATALOGS	eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf Bussmann series complete full line catalog no. 1007
DECLARATIONS OF CONFORMITY	eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf
TECHNICAL DATA SHEETS	720115 Cylindrical fuses



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

