

Specifications



Photo is representative

Eaton QA1633T480

Eaton pringle bolted pressure switch,
Manual bolted pressure contact switch,
1600A, Top, Fusible, 480V, NEMA 1/3R/4/12,
Three-pole, Three-wire

General specifications

PRODUCT NAME	Eaton pringle bolted pressure switch
CATALOG NUMBER	QA1633T480
UPC	782116899852
PRODUCT LENGTH/DEPTH	13.5 in
PRODUCT HEIGHT	28 in
PRODUCT WIDTH	24 in
PRODUCT WEIGHT	160 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed
CATALOG NOTES	For QA switches, use 480V system catalog number when referencing a 208V system. Voltage Control, Ground Fault, Phase Failure Relay, and Control Power Transformer not an option for QA Type Switches.



Powering Business Worldwide

Physical Attributes

FEED TYPE	Top
FUSE CONFIGURATION	Fusible
NUMBER OF POLES	Three-pole
NUMBER OF WIRES	3
SWITCH TYPE	Manually operated contact switch
TYPE	Manual bolted pressure contact switch

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
MULTIMEDIA	Switching Devices Flex Center Double Up on Safety Eaton Switching Devices ARMS Enclosed Circuit Breaker
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - QA1633T480

Performance Ratings

AMPERAGE RATING	1600A
NEMA RATING	NEMA 1, NEMA 3R, NEMA 4, NEMA 12
PROTECTION	Fusible
VOLTAGE - MAX	480 V
VOLTAGE RATING	480 V

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.