Specifications







Eaton C14G50

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 50 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder

General specifications	
PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C14G50
UPC	051712754422
EAN	5027590494120
PRODUCT LENGTH/DEPTH	51 mm
PRODUCT HEIGHT	14.3 mm
PRODUCT WIDTH	14.3 mm
PRODUCT WEIGHT	20.6 g
WARRANTY	1 year limited
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269
GLOBAL CATALOG	C14G50



Due di est en e dification	
Product specification	S
AMPERAGE RATING	50 A
FUSE SIZE	14 x 51 mm
CURRENT TYPE	AC
BREAKING CAPACITY	120 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	400 V
CLASS	Class C gL/gG
FUSE TYPE	C14G
UTILIZATION CATEGORY	gG (cable protection/equipment protection)
FUSE INDICATOR	Other
WATT LOSSES	4.8 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	14 mm x 51 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CH14 Modular fuse holder
MATERIAL	Ceramic
MOUNTING METHOD	14 x 51 mm CH Modular fuse holder
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	400 V
ТҮРЕ	fuse
APPLICATION	for industrial applicationsfor general purpose use

Resources	
CATALOGS	eaton-product-overview- for-machinery-catalogue- ca08103003zen-en-us.pdf
	eaton-bussmann-series- low-voltage-fuses-catalog- ca134002en-en-us.pdf
	Bussmann series complete full line catalog no. 1007
DECLARATIONS OF CONFORMITY	eaton-low-voltage- cylindrical-fuse- declaration-of-conformity- uk250946en.pdf eaton-low-voltage- cylindrical-fuse- declaration-of-conformity- eu250463en.pdf
TECHNICAL DATA SHEETS	720115 Cylindrical fuses

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









