

Specifications



Eaton PV-315A-3L-15

Eaton Bussmann series Fuse-link, high speed, 315 A, DC 1500 V, 3L, 75 x 91 x 205 mm, gPV, UL, IEC, with indicator, blade connections

General specifications

PRODUCT NAME	Eaton Bussmann series photovoltaic fuses
CATALOG NUMBER	PV-315A-3L-15
UPC	051712372169
EAN	5996516001165
PRODUCT LENGTH/DEPTH	217 mm
PRODUCT HEIGHT	82 mm
PRODUCT WIDTH	94 mm
PRODUCT WEIGHT	2035 g
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC 60269 UL Listed CSA Certified



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	315 A
VOLTAGE RATING	1500 Vdc
INTERRUPT RATING	100 kAIC
CLASS	Class gPV
PRE ARC (I2T)	150000
WATT LOSSES	52 W

Compatible fuse holder

SUITABLE FOR	SD3L-S-PV XL Fuse base
--------------	------------------------

Product specifications

APPLICATION	Photovoltaic array combiners and disconnects
FUSE TYPE	PV-3L-15
FUSE INDICATOR	Top fuse status indicator
FUSE SIZE	3L
FITTED WITH:	Blade with top indicator

Resources

CATALOGS	eaton-bussmann-series-photovoltaic-fuses-catalogue-ca135004en.pdf Bussmann series complete full line catalog no. 1007
DECLARATIONS OF CONFORMITY	eaton-high-speed-photovoltaic-fuse-declaration-of-conformity-uk250899en.pdf eaton-high-speed-photovoltaic-fuse-declaration-of-conformity-eu250021en.pdf
MCAD MODEL	eaton-solar-fuses-mcad-3d-models-pv-3l.stp
MULTIMEDIA	Eaton Bussmann - Products for sustainable energy
PRODUCT PAGE (WEB)	Datasheet - PV-125A-2XL
TECHNICAL DATA SHEETS	10201 XL PV fuses

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.