

Specifications

Eaton FWH-3.15A6F

Eaton Bussmann series FWH high speed fuse, 1000 Vac, 800 Vdc, 3.15A, 50 kAIC at 0.25-20A, 20 kAIC at 25-30A, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWH-3.15A6F
UPC	051712796668
EAN	5027590499613
PRODUCT LENGTH/DEPTH	33 mm
PRODUCT HEIGHT	7 mm
PRODUCT WIDTH	7 mm
PRODUCT WEIGHT	2.9 g
WARRANTY	Not Applicable
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Recognized CSA Certified
GLOBAL CATALOG	FWH-3.15A6F



Powering Business Worldwide

Product specifications

AMPERAGE RATING	3.15 A
BREAKING CAPACITY	50 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
FUSE INDICATOR	Other
RELEASE CHARACTERISTIC	Other
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
RATED VOLTAGE AC	500 V
CLASS	Class aR
CLEARING (I2T)	7.7 at 500 V
WATT LOSSES	2.9 W
RESPONSE TIME	>30 min at 150%, <30 min at 200%, <= to 10 sec at 300%
FUSE SHAPE	Cylindrical
PRE ARC (I2T)	3.1
INTERRUPT RATING	50 kAIC
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	Other 6.3 x 32 mm
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	500 V
TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
FUSE TYPE	FWH-A6F
BREAKING CAPACITY AT NOMINAL VOLTAGE, AC	50 kA

Resources

CATALOGS	eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf Bussmann series complete full line catalog no. 1007
MCAD MODEL	eaton-hs-round-body-fuses-mcad-3d-models-fwH-0-25-7a-6f.stp

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.