

Specifications

Eaton FWX-3A14F

Eaton Bussmann series FWX high speed fuse, 600V, 3A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWX-3A14F
UPC	051712795159
EAN	5027590501408
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	35 mm
PRODUCT WIDTH	89 mm
PRODUCT WEIGHT	21.8 g
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Recognized
GLOBAL CATALOG	FWX-3A14F



Powering Business Worldwide

Product specifications

AMPERAGE RATING	30 A
ACCESSORIES	<ul style="list-style-type: none">• CH14 Modular fuse holder• FW14-PCB
BREAKING CAPACITY	200 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
FUSE INDICATOR	Non Indicating
RELEASE CHARACTERISTIC	Other
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC/DC
FUSE SIZE	14 x 51 mm
RATED VOLTAGE AC	250 V
CLASS	Class aR
WATT LOSSES	2.8 W
FUSE SHAPE	Cylindrical
INTERRUPT RATING	200 kAIC
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	14 mm x 51 mm
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	690 V
TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
FUSE TYPE	FWX-A14F
BREAKING CAPACITY AT NOMINAL VOLTAGE, AC	200 kA

Resources

CATALOGS	eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf Bussmann series complete full line catalog no. 1007
MCAD MODEL	eaton-hs-round-body-fuses-mcad-3d-models-fwx-1-50a-14f.stp
TECHNICAL DATA SHEETS	eaton-bussmann-series-fwx-ferrule-high-speed-fuses-datasheet-720006-en-gb.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.