Specifications

Eaton EATS30P

Eaton ATS rack PDU, 1U, (2) L6-30P input, 5.76 kW max, 208-240V, 24A, 10 ft cord, Single-phase, Outlets: (1) L6-30R

General specifications

PRODUCT NAME	Eaton ATS PDU
CATALOG NUMBER	EATS30P
UPC	743172078520
PRODUCT LENGTH/DEPTH	13.8 in
PRODUCT HEIGHT	1.7 in
PRODUCT WIDTH	17.3 in
PRODUCT WEIGHT	22 lb
WARRANTY	3 year
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	UL Listed

Physical

MOUNTING DIRECTION	Horizontal
COLOR	Black
FORM FACTOR	1U
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Electrical input

INPUT CONNECTION	L6-30P
CORD LENGTH	5 ft
WATTAGE	5.76 kW max
AMPERAGE RATING	24A
INPUT VOLTAGE	208-240V
PHASE	Single-phase
FREQUENCY RATING	50-60 Hz

Electrical output

OUTLETS	(1) L6-30R
CIRCUIT BREAKER	None
OUTLET CONTROL	No

Communications

ETHERNET INTERFACE	Yes
SERIAL INTERFACE	Y

Additional specifications

SERIES	eATS

Resources

DRAWINGS	Eaton eATS 30P technical drawing
END OF LIFE NOTIFICATIONS	End-of-life notification for select Eaton rack ATS models
MANUALS AND USER GUIDES	Eaton eATS30 ePDU monitored manual Eaton T2235 series eATS ePDU
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EATS30P

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.