

Specifications



Photo is representative

Eaton T20P11S3716CU

Eaton General purpose ventilated transformer, DS-3 (1-phase), PV 240 x 480V, Taps: 1 at +5%/2 at -5% x 2 at +2.5%/4 at -2.5%, SV 120/240V, 150°C rise, 37.5 kVA, 16, Copper windings

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	T20P11S3716CU
UPC	786680211959
PRODUCT LENGTH/DEPTH	24.38 in
PRODUCT HEIGHT	38.7 in
PRODUCT WIDTH	23.51 in
PRODUCT WEIGHT	525 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEMA TP-1 Compliant DOE2016 Efficient
CERTIFICATIONS	UL Listed
CATALOG NOTES	DOE 2016 Efficient



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Copper
FRAME	818
TAP SIZE	1 at +5% FCAN, 2 at -5% FCBN x 2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous

WEATHERSHIELD	WS11
----------------------	------

Performance Ratings

FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	240 x 480 V
SECONDARY VOLTAGE	120/240 V
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	37.5 kVA

Resources

BROCHURES	Eaton's low-voltage dry-type distribution transformers Eaton's high-efficiency dry-type transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - T20P11S3716CU

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.