

# Specifications



Photo is representative



## Eaton R5A3030U

Eaton rotary disconnect switch, 30 A, Non-fusible, Three-pole, Rotary switch, R5 Series, 600 V

### General specifications

<b>PRODUCT NAME</b>	Eaton rotary disconnect switch
<b>CATALOG NUMBER</b>	R5A3030U
<b>UPC</b>	786685402871
<b>PRODUCT LENGTH/DEPTH</b>	2.57 in
<b>PRODUCT HEIGHT</b>	3.35 in
<b>PRODUCT WIDTH</b>	1.77 in
<b>PRODUCT WEIGHT</b>	0.5 lb
<b>WARRANTY</b>	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>COMPLIANCES</b>	CCC Marked
<b>CERTIFICATIONS</b>	CSA Certified IEC Rated EN Listed UL 508
<b>CATALOG NOTES</b>	Suitable as motor disconnect



Powering Business Worldwide

## Physical Attributes

NUMBER OF POLES	Three-pole
SERIES	R5

## Miscellaneous

PRODUCT CATEGORY	Rotary Switch
------------------	---------------

## Performance Ratings

AMPERAGE RATING	30A
VOLTAGE RATING	600 V

## Resources

CATALOGS	<a href="#">Commercial Distribution, Switching Devices, Volume 2, Tab 1</a>
MULTIMEDIA	<a href="#">Switching Devices Flex Center</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - R5A3030U</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

