

Specifications

Eaton EBA307-06



Eaton Basic rack PDU, 0U, 309-460P9 input, 17.3 kW max, 200-240V, 45A, 6 ft cord, Three-phase, Outlets: (21) C13 Outlet grip, (12) C19 Outlet grip

General specifications

PRODUCT NAME	Eaton basic PDU
CATALOG NUMBER	EBA307-06
UPC	786685931678
PRODUCT LENGTH/DEPTH	66.5 in
PRODUCT HEIGHT	2.1 in
PRODUCT WIDTH	2.05 in
PRODUCT WEIGHT	18.55 lb
WARRANTY	3 year
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	UL Listed



Powering Business Worldwide

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	No
PHASE	Three-phase
WATTAGE	17.3 kW max
AMPERAGE RATING	45A
INPUT VOLTAGE	200-240V
INPUT CONNECTION	309-460P9
OUTLETS	(21) C13 Outlet grip, (12) C19 Outlet grip
CORD LENGTH	6 ft
FREQUENCY RATING	50-60 Hz
ETHERNET INTERFACE	No
SERIAL INTERFACE	No
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton RoHS declaration of conformity: ePDU G3
	Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton ePDU EBA307-06 technical drawing
INSTALLATION INSTRUCTIONS	Eaton ePDU G3 troubleshooting guide
MANUALS AND USER GUIDES	Eaton ePDU G3 replace and configure eNMC module
	Eaton ePDU G3 installation and connectivity quick start
	Eaton ePDU G3 operations manual
	Eaton ePDU G3 1U and 2U installation addendum
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EBA307-06

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

