

Specifications



Photo is representative

Eaton T29M11S1516

Eaton General purpose ventilated transformer, DS-3 (1-phase), PV 208V, Taps: 2 at +2.5% /4 at -2.5%, SV 120/240V, 150°C rise, 15 kVA, 16

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	T29M11S1516
UPC	786680210938
PRODUCT LENGTH/DEPTH	18.39 in
PRODUCT HEIGHT	31.3 in
PRODUCT WIDTH	22.89 in
PRODUCT WEIGHT	226 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEMA TP-1 Compliant
CERTIFICATIONS	UL Listed
CATALOG NOTES	NEMA TP-1 efficient



Powering Business Worldwide

Physical Attributes	
COIL MATERIAL	Aluminum
FRAME	816
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

Miscellaneous	
WEATHERSHIELD	WS11

Performance Ratings	
FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	208 V
SECONDARY VOLTAGE	120/240 V
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	15 kVA

Resources	
BROCHURES	Eaton's low-voltage dry-type distribution transformers
	Eaton's high-efficiency dry-type transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - T29M11S1516

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

