

Specifications



Photo is representative



Eaton S611D242P3S

Reduced Voltage Motor Starters-S611 Soft Starter, Pump, Rating: 75 hp at 208V, 75 hp at 240V, 200 hp at 480V, 250 hp at 600V, 242A, Three-phase, D-frame

General specifications

PRODUCT NAME	Eaton S811+/S801+ soft starter
CATALOG NUMBER	S611D242P3S
UPC	786685480473
PRODUCT LENGTH/DEPTH	21.01 in
PRODUCT HEIGHT	8.57 in
PRODUCT WIDTH	11.58 in
PRODUCT WEIGHT	38 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	IEC 60947-2 CSA Std. C22.2 No.235 UL 1077

Product specifications

AMPERAGE RATING	242A
HP RATING - MAX	75 hp at 208V, 75 hp at 240V, 200 hp at 480V, 250 hp at 600V
PHASE	Three-phase
TYPE	Pump
FRAME SIZE	D

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1 Product Range Catalog Drives Engineering
MULTIMEDIA	Soft Starter Product Family Overview Soft starter DS7 up to 200 A Soft Starter DS7 up to 32 A
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S611D242P3S

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.