

Specifications



Photo is representative

Eaton T29M11S2516

Eaton General purpose ventilated transformer, DS-3 (1-phase), PV 208V, Taps: 2 at +2.5% /4 at -2.5%, SV 120/240V, 150°C rise, 25 kVA, 16

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	T29M11S2516
UPC	786680208492
PRODUCT LENGTH/DEPTH	17.4 in
PRODUCT HEIGHT	33.75 in
PRODUCT WIDTH	22.45 in
PRODUCT WEIGHT	234 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	DOE2016 Efficient
CERTIFICATIONS	UL Listed
CATALOG NOTES	DOE 2016 efficient



Powering Business Worldwide

Physical Attributes

COIL MATERIAL	Aluminum
FRAME	818
INSULATION	220 °C
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer
WIRING CONNECTION	E0260A

Miscellaneous

WEATHERSHIELD	WS45A
----------------------	-------

Performance Ratings

EFFICIENCY	10 CFR Part 431-2016 (DOE 2016)
FREQUENCY RATING	60 Hz
KVA RATING	25 kVA
PRIMARY VOLTAGE	208 V
SECONDARY VOLTAGE	120/240 V
SOUND LEVEL	NEMA ST-20
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	25 kVA

Resources

	Eaton's high-efficiency dry-type transformers
BROCHURES	Eaton's low-voltage dry-type distribution transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - T29M11S2516

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

